

the REFLECT-R Advantage



Better Protection from external heat

REFLECT-R's pure aluminum facing reflects 97% of radiant heat gain.

Faster Onsite installation

The rigidity of the 3/4" core, heavy duty reinforced facing and various tab options designed for every application will save you many man hours on the jobsite.

Safer In-place fire protection

REFLECT-R's fiberglass core reduces the risk of fire spread as compared to many non-fiberglass core reflective insulations.

REFLECT-R is ASTM E84 and UL723 approved. REFLECT-R achieved a 25/50 rating which provides a Class A / Class 1 rating.

PLANT LOCATIONS

Cleveland, OH • Lancaster, PA • Madison, WI
Atlanta, GA • Phoenix, AZ • Dallas, TX
Stockton, CA • Kent, WA • Spokane, WA

CORPORATE OFFICE

31387 Industrial Parkway
North Olmsted, OH 44070
888-248-7858



THERM-ALL

Insulation Doesn't Cost, It Pays.

www.therm-all.com

REFLECT-R *Get the Facts...*

Product Standards

Widths: 72"

Lengths: 80'

Thickness: 3/4" standard, 1" optional

Tabs: 2-3" staple or 1-6" tab standard, optional 1-6" tab with double stick tape

Foil Facing: 99.9% pure aluminum (standard)

Non-Foil Facing: PSK-VR (optional – reduces R-value)

Stated R-Values

		Down:	Up:	Horizontal:
3/4" Thick:	FGF	11.6	7.0	8.5
	FGVR	7.8	5.4	6.0
1" Thick:	FGF	11.8	8.2	10.1
	FGVR	8.4	7.4	6.4

To achieve and maintain R-values, product must be installed per manufacturer instructions.

Summer Heat Gain

Convection
0%

Conduction



3%
to
7%

Radiation



Up to
93%

Heat is transferred through three different processes: convection, conduction and radiation. Of these three, radiation creates 93% of summer heat.

How is the R-Value determined?

The FTC (Federal Trade Commission) requires reflective insulation R-Values to be determined by using the ASTM C 1224 test. This test determines an R-Value for the entire assembly. The assembly consists of two 2"x4" wood studs 16" on center, 1/2" plywood deck on top and the insulation installed at the mid-span of the 2"x4". The reflective airspace is critical to creating R-Value. The greater the airspace, the greater the R-Value.

How can other brands of reflective insulation claim to have a greater R-Value?

Some suppliers still use the ASTM C976 test which allows them to place the insulation on the outside edge of the 2"x4", thus creating a 3 1/2" air space. In July of 2003, the FTC ruled to no longer accept the ASTM C976 test as a "fair and accurate" test in establishing R-Values.

REFLECT-R Results:

- Infrared waves create radiant heat
- The waves travel at the speed of light, in straight lines
- With Reflect-R insulation, 97% of these waves are deflected



THERM-ALL
Insulation Doesn't Cost, It Pays.

PLANT LOCATIONS

Cleveland, OH • Lancaster, PA • Madison, WI
Atlanta, GA • Phoenix, AZ • Dallas, TX
Stockton, CA • Kent, WA • Spokane, WA

CORPORATE OFFICE

31387 Industrial Parkway
North Olmsted, OH 44070

Call us at 888-246 7858 or
visit us at www.therm-all.com

